



C1304/3652



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 14 SEP 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew

Dated

2 September 2004

BEST AVAILABLE COPY

THE PATENT OFFICE
NA
29 AUG 2003
RECEIVED BY FAX

The
Patent
Office

29AUG03 0833722-1 002887
P01/7700-0.00-0320285.0

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

XA1807

2. Patent application number

(The Patent Office will fill in this part)

0320285.0

29 AUG 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

BAE SYSTEMS plc

6 Carlton Gardens
London, SW1Y 5AD

Patents ADP number (if you know it)

07914674004 ✓

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

RETROREFLECTIVE DEVICES

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

BAE SYSTEMS plc
Group IP Department
Lancaster House, P.O. Box 87
Farnborough Aerospace Centre
Farnborough, Hampshire, GU14 6YU

Patents ADP number (if you know it)

07914674002 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number.

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

<p>THE PATENT OFFICE NA 29 AUG 2003 RECEIVED BY FAX</p>	Continuation sheets of this form	
	Description	08
	Claim(s)	03
	Abstract	01
	Drawing(s)	04

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) **1**

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature Anurddha Mukherjee Date 29 August 2003

Anurddha Mukherjee

29 August 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Maria Burkes 01252 383487

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

DUPLICATE

XA1807

1

RETROREFLECTIVE DEVICES

This invention relates to retroreflective devices; the term "retroreflective devices" as used herein being intended to encompass generally optical components used for returning radiation automatically from a remote location toward an optical source.

Retroreflective devices are designed to reflect radiation back towards its source, and such devices are thus frequently used to return radiation toward radiating optical sources when it is inconvenient or undesirable to actively generate radiation at locations, remote from the optical sources, which need to send response radiation to fixed or mobile base locations at which the radiating optical sources are sited. Common examples include the use of special reflective materials for safety clothing or signage, cat's eye markers in road surfaces, and measurement points in land surveying or robotic machinery. Retroreflective devices may also be used in combination with optical modulation mechanisms in order to establish two-way optical communication between the base station and the remote location without needing an optical source at the remote end of the link.

Retroreflective devices currently in common use can be classified into two main types.

The first of these accomplishes retroreflection without any focusing of the incoming radiation from the source. This type is commonly available as a component with a set of three mutually perpendicular reflecting surfaces, and is known as a "corner-cube" retroreflector. Different embodiments of this type of reflector exist, but all require very high quality in the reflecting surfaces, which also need to be very accurately assembled in order to provide precise angular coincidence between the incident and reflected beams. Consequently, such components are expensive to make, but they have the advantage of providing diffraction limited performance which gives excellent quality to the reflected beam. Disadvantageously, however, such devices exhibit a limited field of view which varies with the construction details, but which cannot allow coverage of arbitrary angles of incidence across a full hemisphere without grouping several

reflectors together, where each reflector is pointed in a different direction. This increases the expense and the complexity of constructing such devices with high field of view.

The second type of retroreflective device currently in common use employs focusing of the incident radiation onto a primary reflecting surface. This type is known as a "cat's eye" retroreflector, and commonly employs glass spheres, or cemented hemispheres, in order to provide retroreflection for paraxial incident rays. Such devices can be made very small (for example with sub-millimetre diameters) and offer a very wide field of view, including a complete hemisphere or more in a single component. Furthermore, single spheres can be manufactured in quantity at low cost. The main disadvantage of this design is that the reflected radiation is subject to severe spherical aberration for non-paraxial rays, and this can strongly reduce the far-field intensity of the reflected beam measured on-axis. It also leads to significant beam divergence, making the reflection visible far from the axis, which can be undesirable in some applications, for example in free-space communication where privacy is desired.

A class of lenses, called 'graded refractive index' (or GRIN) lenses, is known, in which the material of the lens exhibits gradual variations in refractive index through its volume. An example is the so-called "GRIN-rod" lens, which is a graded-index lens with cylindrical symmetry and radial parabolic index distribution. See S. Nemoto and J. Kida, 'Retroreflector using gradient-index rods' Appl. Opt. 30(7), 1 Mar 1991, p.815-822.

In a publication entitled "Gradient Index Optics" published by Academic Press in 1978, E.W. Marchand describes at pages 2 and 3 a lens, previously discovered by Luneburg, having an index function with spherical symmetry about a point. Marchand describes the Luneburg lens as difficult to make (at least for radiation in the visible region of the spectrum), and goes on to say that the lens, even if it can be made, has limited possibilities for useful application, though he does suggest a possible modification of the lens, incorporating a mirror to produce an action similar to that of a corner cube.

Sphere lenses with refractive index distributions possessing spherical symmetry are known as 'GRIN-sphere' lenses, having a spherically symmetric

refractive index distribution in which the refractive index varies gradually across a radial cross-section. Such lenses are known to exhibit improved spherical aberration compared to uniform sphere lenses. See Y. Koike, A. Kanemitsu, Y. Shioda, E. Nihei and Y. Ohtsuka, 'Spherical gradient-index polymer lens with low spherical aberration' Appl. Opt. 33(17), 1 Jun 1994, p. 3394-3400.

GRIN-rod lenses have been proposed for use in retroreflective devices, but these lenses suffer from restrictions on field of view similar to those exhibited by corner-cube retroreflectors. Other types of cat's eye retroreflector can be based on catadioptric lens designs, but these also share the aforementioned restrictions on field of view.

The present invention aims to address at least one of the above-identified disadvantages associated with the retroreflective devices currently in common use. Preferred embodiments of the invention aim to overcome, or at least reduce, the spherical aberration experienced in cat's eye retroreflectors based on conventional sphere lenses while retaining, at least in substantial measure, their benefits of wide field of view compared to corner-cube retroreflectors.

According to one aspect of the invention there is provided a retroreflective device comprising a substantially spherical graded refractive index lens, a reflective part for retroreflecting a radiation beam passing through the graded refractive index lens and, at least partially surrounding the lens, a non-gaseous transparent material having a substantially uniform refractive index.

The provision of a transparent material of substantially uniform refractive index outside the lens provides for increased ease of manufacture of the device when the refractive index of the refractive material is substantially greater than unity. The GRIN-sphere lens can then have a refractive index variation which need not be as large as would otherwise be required. Further, by use of the present invention, the refractive index at the outer surface of the lens need not be matched to that of an air interface, which is practically impossible, particularly in the visible and infra-red regions of the spectrum, in which the present invention has particular application.

Preferably, the refractive index distribution of the GRIN-sphere lens has a spherical aberration reducing effect. The invention may be employed where the

XA1807

4

focusing action of a low-aberration sphere in air is not strong enough to provide convergence of the incident beam to a point on the rear surface of the sphere itself, or if sufficiently low aberration for a particular application cannot be achieved using a GRIN-sphere in air.

- 5 In preferred embodiments, the transparent material surrounds a substantial part of the lens. In a particularly preferred embodiment, the transparent material surrounds at least approximately one half of the lens, and more preferably surrounds substantially the entire lens.

Note that, herein, the term "spherical" is intended to refer to surfaces
10 which include both whole spheres and part-spherical surfaces.

The boundary of the transparent material remote from the lens is, in some preferred embodiments of the invention, defined by a substantially spherical surface and in other preferred embodiments the boundary is defined by a substantially planar surface, although any configuration of the boundary can be
15 used if selected to perform a particular optical purpose.

In order that the invention may be clearly understood and readily carried
20 into effect, some embodiments thereof will now be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1 shows a retroreflective device in accordance with a first
20 embodiment of the invention;

Figure 2 shows a retroreflective device in accordance with a second embodiment of the invention;

Figure 3 shows a retroreflective device in accordance with a third embodiment of the invention; and

25 Figure 4 shows two exemplary refractive index distributions in accordance with embodiments of the invention.

Referring now to Figures 1 to 3 of the drawings, preferred embodiments of retroreflective devices based on GRIN-sphere lenses are described, by way of example, but it will be appreciated by those skilled in the art that other designs
30 may readily be devised to suit particular objectives.

Figure 1 shows a first embodiment of a retroreflective device based on a GRIN-sphere lens arranged in accordance with the invention. The upper

XA1807

5

hemisphere of the mechanical surface of the GRIN-sphere lens 2, shown as a solid circle 2, is the surface through which an incident radiation beam B (which is assumed to be a parallel beam) passes into the GRIN-sphere lens.

In order to improve the optical characteristics of the device, the GRIN-sphere lens 2 is clad in, or otherwise coated with, a transparent material 4 having a uniform refractive index of a particular, desired value. The transparent material has a uniform thickness, and has an outer spherical surface which is arranged concentric with the outer surface of the GRIN-sphere lens 2. The upper surface of the transparent material forms the entrance face of the device. Although not shown in Figure 1, the entrance face of the transparent material 4 (and indeed the equivalent surfaces shown in other figures hereof) may be provided with an anti-reflective coating, applied in any convenient manner.

A reflective coating 6 is applied directly to the outer surface of the transparent material 4, on the side opposite the entrance face, to provide retroreflection of the incident rays 4 as shown. For optimum field of view, the reflective coating 6 covers approximately a hemisphere on the outer surface.

The lens 2 may be made of suitable polymer materials, such as benzyl methacrylate or similar materials, or glass. The desired refractive index distribution may be obtained by any known technique, such as diffusion of suitable materials within the sphere, or photo-inscription in photosensitive material using, for example, ultra-violet sources.

The transparent material 4 may be made of a suitable plastic, for example polymethyl methacrylate, or glass.

The reflective coating 6 may be metallic, for example aluminium, to provide broad spectral reflection, or can itself be of multi-layer design to provide wavelength selective reflection.

A second embodiment of the invention is shown in Figure 2. Here, components similar to that shown in Figure 1 are given the same reference numerals, incremented by 100. The GRIN-sphere lens 102 is immersed in, and may be at least partially supported by, an environment comprising a transparent solid material 104 of uniform refractive index, having a chosen relationship with the refractive index at the GRIN-sphere surface. The transparent material may be

XA1807

6

supported by a solid structure 108, which may for example have a lower surface formed, for example as a planar surface, so as to stably support the device in a preferred orientation on a horizontal surface.

Alternatively, depending for example upon the use for which the device is intended and/or the treatment to which it may be subjected, the lens may be immersed in a transparent liquid material and supported by thin filaments (not shown) stretched from the supporting structure 108.

The entrance face 110 of the transparent material 104, forming a boundary of the transparent material remote from the lens 102, and through which a radiation beam passes to be retroreflected, is in this embodiment defined by a substantially planar surface. Such a form of entrance face is relatively easy to manufacture, and does not require precise alignment with respect to the GRIN-sphere lens 202. However, such a form of entrance face suffers from angularly-dependent retroreflectivity and polarisation effects.

Figure 3 shows a third embodiment of the invention, which reduces angularly-dependent retroreflectivity and polarisation effects. Here, components similar to those previously described have the same reference numerals, incremented by 100. The transparent material 204 is given a hemispherical outer shape. The material may in this embodiment be protected by a transparent-optical

dome casing (not shown) made of a relatively hard material, such as glass. This arrangement reduces the variation of reflection performance with incidence angle, compared to the embodiment shown in Figure 2. The rays encountering the GRIN-sphere can be made effectively paraxial with respect to the lens formed by the outer surface 210, provided that the radius of curvature of the outer surface is made sufficiently large compared to the radius of the outer surface of the GRIN-sphere lens 202. Due to the preferred relatively large radius of curvature of the outer surface of the transparent material 204 at the entrance face 210, the reflective surface of the reflective material 206 has a smaller radius of curvature than that of the entrance face 210.

Figure 4 shows two exemplary refractive index distributions of the GRIN-sphere lens, which may be used in any of the first to third embodiments of the invention.

The distributions are plotted across the entire (normalised) radius of the GRIN-sphere lens, ranging from 0 to 1. The refractive index of the GRIN-sphere lens at each radial point is normalised with respect to the refractive index of the transparent material. In the lower one of the two illustrated distributions, the refractive index ranges from a minimum of approximately 1.02 near the outer surface of the GRIN-sphere lens to approximately 1.10 at the centre of the GRIN sphere lens. In the upper one of the two illustrated distributions, the refractive index ranges from a minimum of approximately 1.08 near the outer surface of the GRIN-sphere lens to approximately 1.14 at the centre of the GRIN sphere lens.

Each of the two exemplary refractive index distributions includes parts having at least two separate radial extents within which the material of the GRIN-sphere lens has a continuously varying refractive index, the refractive index variation having a gradient discontinuity between the two radial extents. The discontinuity is the minimum shown near the outer surface of the lens.

Each of the two exemplary refractive index distributions provides a GRIN-sphere lens having a refractive index at its centre which is greater than a refractive index at its outer surface. Further, it can be seen that the transparent material has a refractive index which is less than a refractive index of GRIN-sphere lens at its outer surface.

Preferably, the ratio of the refractive index of GRIN-sphere lens at its outer surface to the refractive index of the transparent material is between 1 and 2, for example between 1.02 and 1.2. Further preferably, the ratio of the refractive index of GRIN-sphere lens at its centre to the refractive index of the transparent material is between 1 and 2, for example between 1.05 and 1.5.

Typically, in embodiments of the invention, the GRIN-sphere lens has a refractive index distribution which averages, across a radial cross-section, between 1.4 and 1.8, and the transparent material has a refractive index greater than 1.3.

The transparent material as described in each of the above embodiments is preferably formed, for example as two interfitting halves, by a moulding process. In this manner, the material can be accurately shaped to support the GRIN-sphere lens concentrically with respect to its inner and outer spherical

surfaces. Alternative procedures may of course be used depending upon various criteria, such as overall dimensions, performance requirements and operational demands such as robustness.

- 5 The above embodiments are to be understood as illustrative examples of the invention. It is to be understood that any feature described in relation to any one embodiment may be used alone, or in combination with other features described, and may also be used in combination with one or more features of any other of the embodiments, or any combination of any other of the embodiments. Furthermore, equivalents and modifications not described above may also be employed without departing from the scope of the invention, which is defined in
- 10 the accompanying claims.

1078555 29 Aug 03 05:34

CLAIMS

1. A retroreflective device comprising a substantially spherical graded refractive index lens, a reflective part for retroreflecting a radiation beam passing through the graded refractive index lens and, at least partially surrounding the lens, a non-gaseous transparent material having a substantially uniform refractive index.

2. A device according to claim 1, wherein said graded refractive index lens has a gradually varying, spherically symmetric, refractive index distribution.

3. A device according to claim 2, wherein said refractive index distribution includes parts having at least two separate radial extents within which the material of the lens has a continuously varying refractive index, the refractive index variation having a gradient discontinuity between said two radial extents.

4. A device according to any preceding claim, wherein said graded refractive index lens has a refractive index at its centre which is greater than a refractive index at its outer surface.

5. A device according to any preceding claim, wherein said transparent material has a refractive index which is less than a refractive index of said graded refractive index lens at its outer surface.

6. A device according to any preceding claim, wherein a ratio of the refractive index of said graded refractive index lens at its outer surface to a refractive index of said transparent material is between 1 and 2.

7. A device according to any preceding claim, wherein a ratio of the refractive index of said graded refractive index lens at its centre to a refractive index of said transparent material is between 1 and 2.

5 8. A device according to any preceding claim, wherein said transparent material surrounds at least approximately one half of the lens.

9. A device according to any preceding claim, wherein at least part of said transparent material is located between said graded refractive index lens and
10 the reflective part.

10. A device according to any preceding claim, wherein said reflective part includes a substantially spherical reflective surface arranged concentrically with respect to said graded refractive index lens.

15

11. A device according to any preceding claim, wherein a boundary of the transparent material remote from said lens, and through which a radiation beam passes to be retroreflected, is defined by a substantially spherical transparent surface arranged concentrically with respect to the graded refractive
20 index lens.

25

12. A device according to claim 10 and 11, wherein said substantially spherical reflective surface and substantially spherical transparent surface have substantially the same radius of curvature.

25

13. A device according to claim 10 and 11, wherein said substantially spherical reflective surface and substantially spherical transparent surface have different radii of curvature.

30

14. A device according to claim 13, wherein said substantially spherical reflective surface has a smaller radius of curvature than that of said substantially spherical transparent surface.

15. A device according to any of claims 1 to 10, wherein a boundary of the transparent material remote from said lens, and through which a radiation beam passes to be retroreflected, is defined by a substantially planar surface.

5

16. A device according to any preceding claim, wherein said transparent material comprises a solid moulded component.

17. A device according to any preceding claim, wherein said
10 transparent material has a refractive index greater than 1.3.

18. A device according to any preceding claim, wherein said graded refractive index lens has a refractive index distribution which averages, across a radial cross-section, between 1.4 and 1.8.

15

ABSTRACT

RETROREFLECTIVE DEVICES AND SYSTEMS

- 5 A retroreflective device comprising a substantially spherical graded refractive index lens, referred to as a GRIN-sphere lens, a reflective part for retroreflecting a radiation beam passing through the graded refractive index lens and, at least partially surrounding the lens, a transparent material having a substantially uniform refractive index.

10

1/4





Fig. 1

**Fig. 2**





Fig. 3

4/4

**Fig. 4**

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.